



Leather Repair Company

Contact Us

Leather Repair Company
Unit 22, Argyle Street Factory Estate,
Hull, East Yorkshire, England, HU3 1HD

 +44 (0) 1482 606 864

 leatherrepaircompany.com

 help@leatherrepaircompany.com

LRC36 – Leather Primer

Leather Primer is designed to give better adhesion to painted surfaces, when applying leather colour repair paint.

The leather primer is a clear coating when applied that is used to bond paint to the leathers surface, it's applied to bare leather.

Preparation is key for this product to work correctly; you must remove the surface colour first before this can be applied.

For smaller areas, this can be sponged on to the leather surface, you will need to sponge on several coats. This can be dried with a hairdryer between coats, when dry this product feels sticky to the touch, it needs to be sticky so that the paint will bond to it better.

Small areas are considered to be no more than 12 inches long by around 6 inches wide

For areas that are bigger than the above it's best to be spray applied. Spray at around 6 to 8 inches away from the surface, do not flood the area with this product. Apply thin layers allowing each layer to dry between coatings, each coating should dry and be sticky to touch when dried.

You should only need to apply three coatings of the leather primer onto the surface.

This can be used on most leather surfaces, if you are turning aniline leather to a pigmented leather, then this can be used for that purpose to give better adhesion of the paint to the aniline leather surface.

If you are dealing with vinyl this will require a different product, this is called [vinyl adhesion promotors](#).

Always wear a mask when using this product if being sprayed on, wear gloves at all times and goggles if spraying.

If you need to remove the leather primer in case you have made a mistake, then you can use a red scotch pad and leather prep to lightly rub over the surface to remove the product so you can start again from the start. Once removed clean the area down with alcohol cleaner, then start the application again.

Take a look at the [YouTube Video](#) about this product.

Available sizes, 250ml – 8.5 fl oz, 500ml – 17 fl oz, 1ltr – 34 fl oz, 5ltr – 176 fl oz

Use Within, Use within 24 months of purchase.

Manufacturers Warranty 12 months from point of sale.

Temperatures, do not allow to freeze or go below 7 °C.

Before Use, always check in a small hidden area before using to ensure its suitability for the leather.

Colour, Opaque cloudy liquid.

Smell, has an alcohol IPA aroma to it.

Drying Time, around 5 minutes depending how thickly applied.

Formula, a solvent based adhesion solution.

Skin Allergies, if you have skin allergies always wear gloves, wear goggles when applying.

Cautions, Harmful if swallowed. Keep out of reach of children, may cause skin irritation. Seek medical attention at once, do not induce vomiting. Avoid contact with eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so, continue rinsing. Use a mask at all times using in a well-ventilated area.

Uses, to act as a bonding agent for paints to bond to bare leather.

Works on these leathers, pigmented leather, top coated leather, aniline leather, semi aniline leather, antique leather, two tone leather, rub-off leather, waxy pull-up leather.

For use on, Car Leather Interiors, Leather Sofas, Leather Chairs, Leather Shoes, Leather Handbags, Leather Briefcases, Leather Saddles, Equine Leather, Leather Jackets, Motorcycle Leathers, Leather Boots, Leather Purses, Leather Trousers. Leather Clothing, Motor Bike Leathers, Leather Walls, Leather Tables, Classic Car Interiors, Marine Leather.