# ALCOHOL CLEANER

Page: 1 Compilation date: 12/08/2008 Revision date: 07/11/2016 Revision No: 5

Sent to: Public Server Addition.

# Section 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

Product name: ALCOHOL CLEANER

REACH registered number(s): 01-2119457558-25

CAS number: 67-63-0

EINECS number: 200-661-7

Index number: 603-117-00-0

Synonyms: IPA

PROPAN-2-OL

ISO PROPYL ALCOHOL

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Industrial uses: Uses of substances as such or in preparations at industrial sites.

Solvent for industrial use. Uses in coatings. Lubricants and lubricant additives. Use in

cleaning agents. Water treatment applications. PC21: Laboratory chemicals.

# 1.3. Details of the supplier of the safety data sheet

# 1.3. Details of the supplier of the safety data sheet

Company	Leather Repair Company	
Address	Unit 22	
	Argyle Street Factory Estate	
	Hull	
	East Yorkshire, HU3 1HD	
	United Kingdom	
Web	www.leatherrepaircompany.com	
Telephone	01482 606864	
Email	info@leatherrepaircompany.com	
Email address of the competent person		
	info@leatherrepaircompany.com	

# 1.4. Emergency telephone number

### 1.4. Emergency telephone number

01482 606864 9.00 am - 5.00 pm Mon - Fri

# Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H336; Eye Irrit. 2: H319; Flam. Liq. 2: H225

Most important adverse effects: Highly flammable liquid and vapour. Causes serious eye irritation. May cause

drowsiness or dizziness.

ALCOHOL CLEANER

Page: 2

### 2.2. Label elements

### Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P243: Take precautionary measures against static discharge.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: PROPAN-2-OL

CAS number: 67-63-0

EINECS number: 200-661-7

REACH registered number(s): 01-2119457558-25

### Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

- Eye contact: Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues
  - Ingestion: Wash out mouth with water. If patient is conscious, give water to drink. If patient feels unwell, seek medical advice.DO NOT INDUCE VOMITING. Get medical attention immediately.

# ALCOHOL CLEANER

**Page:** 3

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Seek

medical attention if necessary.

### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water

spray to cool containers.

## 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Vapour may travel considerable distance to source of ignition and flash back.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

# Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

ignition.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

# ALCOHOL CLEANER

6.4. Reference to other sections

## Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden. Use non-sparking tools.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

8.1. Control parameters

### Workplace exposure limits:

Workplace exposure limits:		Respirable dust		
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m3	1250 mg/m3	-	-

### Hazardous ingredients:

**PROPAN-2-OL** 

### Workplace exposure limits:

i				
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m3	1250 mg/m3	-	-

**Respirable dust** 

# **DNEL/PNEC** Values

### **ISOPROPANOL**

Туре	Exposure	Value	Population	Effect
DNEL	Oral	26 mg/kg bw/day	Consumers	Systemic
DNEL	Dermal	319 mg/kg bw/day	Consumers	Systemic
DNEL	Dermal	888 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	89 mg/m3	Consumers	Systemic
DNEL	Inhalation	500 mg/m3	Workers	Systemic

# ALCOHOL CLEANER

**Page:** 5

PNEC	Fresh water	140.9 mg/l	-	-
PNEC	Fresh water sediments	552 mg/kg	-	-
PNEC	Marine sediments	552 mg/kg	-	-
PNEC	Marine water	140.9 mg/l	-	-
PNEC	Microorganisms in sewage	2251 mg/l	-	-
	treatment			
PNEC	Soil (agricultural)	28 mg/kg	-	-

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Required, if exposure limit is exceeded. In Case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self- contained respiratory protective device. Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Protective gloves should be replaced at first signs of wear. butyl rubber (BR), or

Fluorinated Rubber gloves Glove thickness 0.5mm Breakthrough time of the glove material > 8 hours.

Eye protection: Safety goggles. Safety glasses. Ensure eye bath is to hand.

Skin protection: Solvent resistant protective clothing.

# Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State:	Liquid	
Colour:	Colourless	
Odour:	Alcoholic	
Evaporation rate:	Moderate	
Oxidising:	Non-oxidising (by EC criteria)	
Solubility in water:	Soluble	
Also soluble in:	Most organic solvents.	
Viscosity:	Non-viscous	
Boiling point/range°C:	78-82	Melting point/range°C: -88
Flammability limits %: lower:	2.5	upper: 12.7
Flash point°C:	12	Part.coeff. n-octanol/water: No data available.
Autoflammability°C:	>399	Vapour pressure: 4.16kPa@20c
Relative density:	0.786	pH: Neutral
VOC g/I:	No data available.	

9.2. Other information

Other information: No data available.

# ALCOHOL CLEANER

## Section 10: Stability and reactivity

#### 10.1. Reactivity

#### Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

#### Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

# PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

### Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

#### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# ALCOHOL CLEANER

Page: 7

# Section 12: Ecological information

### 12.1. Toxicity

Ecotoxicity values: No data available.

# 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

### Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

### Section 14: Transport information

14.1. UN number

UN number: UN1219

14.2. UN proper shipping name

Shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

# ALCOHOL CLEANER

Tunnel code: D/E

Transport category: 2

# Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# **Section 16: Other information**

## Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.
\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation. H336:

May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.