



Leather Repair Company

Contact Us

Leather Repair Company
Unit 22, Argyle Street Factory Estate,
Hull, East Yorkshire, England, HU3 1HD

+44 (0) 1482 606 864

leatherrepaircompany.com

help@leatherrepaircompany.com

LRC43 Boiled Linseed Oil

Our boiled linseed oil is suitable for all types of exterior timbers other than oak. It's treated with hot air making it dry faster and have a far superior quality compared to other boiled linseed oils, creating a hardwearing tough barrier on timber and porous stone.

Boiled Linseed Oil can be use on all wooden surfaces both inside and outside. It can be used on every type of wood too, except exterior oak. As well as wood it works on stone, terracotta tiles, garden ornaments, statues, and ornate brick work, works on porous surfaces, providing a great protective barrier and waterproof protection.

Boiled Linseed Oil is suitable for both Interior & Exterior Wood. Fully compliant with 'Articles In Contact With Food' Regulations

This works on Hardwoods and Softwoods, Kitchen Worktops & Utensils, Doors and Windows, Hardwood Floors, Turned Wood, Untreated Timber, Stripped and Bare Wood, Stained but Unfinished Wood.

Ensure all surfaces are cleaned thoroughly and dried before application, the first application can be diluted with turpentine up to 25% of this ensures the linseed oil will penetrate further into the timbers pores and enhance the grain pattern even further, providing a very tough durable coating.

On all porous stone type materials brush off loose debris and clean thoroughly with a dedicated stone or terracotta cleaner and fully dry before application. If you don't have a dedicated stone cleaner a soapy warm water solution can be used.

Instructions

1. Ensure the surface to be treated is cleaned and dried before use.
2. Shake the bottle well before use to ensure it is mixed together.
3. Apply the boiled linseed oil to a lint free cloth and apply in the direction of the grain.
4. Allow the boiled linseed oil to soak into the surface for around 15 to 30 minutes.
5. Wipe away any excess after it's soaked in.
6. Lightly rubbing in between coats with ultra-fine steel wool 0000 grade will improve finished results.

Make sure the surface to be treated is deep cleaned and dried before applying the boiled linseed oil. For natural stone use a dedicated stone cleaner. On timber brush off any green algae and dirt from the timber and allow to dry after cleaning down with a water and soap solution.

Apply in the direction of the grain on all wooden surface, sand lightly between coats to give an even great enhancement of the natural grain pattern, sanding is carried out with a fine grade wool 0000 or a very fine 2000 grit sandpaper foam pad to remove any small blemishes in the surface.

After the first application allow this to dry for approximately 30 minutes and then wipe off any excess with a clean dry lint free cloth.

Allow the boiled linseed oil to fully cure for 24 hours lightly sand and apply an additional coating to enhance the patina of the timber or stone further, this will create an even harder shell of protection on the surface.

Always apply annually to ensure the protection is maintained on all surfaces.

Take a look at the [YouTube Video](#) about this product.

Available sizes, 250ml – 8.5 fl oz, 500ml – 17 fl oz, 1ltr – 34 fl oz, 5ltr – 176 fl oz.

Use Within, Use within 30 months of purchase.

Manufacturers Warranty 12 months from point of sale.

Temperatures, do not allow to freeze or get too hot, store between 7 °C and 20 °C.

Before Use, always check in a small hidden area before using.

Coverage, between 10m² to 20m² per litre depending on absorption.

Colour, Brown type colour.

Smell, Natural strong cooking oil scent.

Formula, Natural flax plant.

Finish, Satin sheen levels.

Skin Allergies, if you have skin allergies always wear gloves.

Cautions, KEEP AWAY FROM SOURCES OF IGNITION. Harmful if swallowed. Keep out of reach of children, may cause skin irritation. Seek medical attention at once, do not induce vomiting. Avoid contact with eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so, continue rinsing.

Discard rags safely lay them flat and allow them to dry fully, do not allow bundles of rags to be left in direct sunlight as they can combust. Do not put rags into a bundle, discard separately.

Uses, to protect timber, stone, slate, terracotta tiles, porous stone, works on plastic trim.

Works on / works on, Hardwoods and Softwoods, Kitchen Worktops & Utensils, Doors and Windows, Hardwood Floors, Turned Wood, Untreated timber, Stripped and Bare Wood, Stained but unfinished wood, Stone, Terracotta, Porous Stones, Cricket Bats and Musical Instruments.